



2008 Peterbilt 330 2000 Gallon Grease Pumper



1) Compartment Aluminum Tank - ¼" #5454 shell and heads – 60" diameter –

Primary moisture trap – 20" top man way – 20" rear cleanout – anti-surge baffles – full length 26" wide hose trays - full length 20" hose protector – rear 3" load line – front 3" load line – rear discharge 4" valve – exterior rings – (3) sight eyes – hose hooks – ladder – vapor proof L.E.D. lights – (2) rear work lights – D.O.T. rear bumper – lifting lugs

- N.V.E. 367 Max Pax 350 CFM
- Hot Shift P.T.O.
- Heavy duty driveline
- Secondary moisture trap
- Oil catch muffler
- Pressure and vacuum relief valves
- 30/30 Gauge
- 4" Brass lever valve with 4" adaptor and dust cap – discharge W/Heated valve
- 3" Brass lever valve with 3" adaptor and dust cap – W/ Heated valve
- External water circulation pump
- Pump stand with right angle gear box and Woods coupling
- Lockable tool box
- Customized operations manual and parts list
- Haney Electric Rewind reel with 75' of two inch suction hose
- Optional heated valves and tank heaters
- Accu Level metering system

Multiple Chassis and Tank sizes available

Call today to spec the perfect grease collection unit for you.