



2008 Sterling Bullet

Available Tank Sizes 800-1500 Gallons

The new Bullet is ready to work when you are. Twenty four hours a day any way you need it. In a two wheel drive or four wheel drive, the Bullet can handle tanks from 800 to 1500 gallons in wheel-bases from 168 to 204 inches. Automatic or Standard transmissions with 50,000 PSI frame rails can take the daily duty of portable toilet servicing.



Cab/Chassis Specifications

Engine: Cummins 6.7I 305HP
 Trans. Auto Asian 6 Speed
 Trans. Standard MB 6 Speed
 Front Axle 7,000 lbs.
 Rear Axle 13,500 lbs.
 GCWR 26,000 lbs

Vacuum System Specifications

Standard Pump: Masport HXL4V 156 CFM
 Primary Moisture Trap, Secondary Moisture Trap
 3" Suction Line, 4" Discharge, Anti Surge Baffles
 Large Waterproof Cabinet Both Sides
 Work Lights, Rear Toilet Carrier, Trailer Hitch
 20" Top Manway, Hose reel with 50' Hose

Weight Distribution (1250 Gallon)

Load	Front Axle*	Rear Axle*	Total*
Fresh Full/Waste Empty	5,600	7,453	13,053
½ Fresh ½ Waste	5,023	10,324	15,347
20% Fresh/ Full Waste	4,644	13,205	17,849

* All Weights include 400lbs, for pump and equipment and 400lbs of portable toilets on rear carrier

Vacuum Pump Performance

	15" HG	20" HG
500 Gallons	18 Seconds	28 Seconds
700 Gallons	25 Seconds	39 Seconds
900 Gallons	31 Seconds	50 Seconds
1100 Gallons	42 Seconds	61 Seconds

Options

Chemical tank, Pressure Washer System, Vacuum Pumps: Masport, Jurop, Moro & NVE
 Dual Service, Additional Hose reels, Hydraulic Pumping Systems, Dual Remote controls
 Pump Flush Kit and scent boxes, Amber beacons, 3rd compartment



Nation Wide Delivery
 Multiple Financing Options
 Outstanding Customer Service and Follow Up

KeeVac Industries Inc.

1865 W. Union Ave. Unit A Sheridan, CO. 80110

866-789-9440

www.keevac.com

